



- Accuracy:  $\pm 0.03\%$  F.S.; Input frequency: 0.001Hz~10KHz
- Measuring Frequency / DC Pulse / Magnetic
- High brightness 0.8" LED display: -19999~99999; decimal point selectable
- Line-Speed / RPM / Frequency selectable
- Line unit: M, Ft, Y/min selectable
- 1~2 Alarms (Hi or Lo) programmable / Analog output (16 bit resolution) / RS-485 communication optional (3 output options select 1)
- High stability, non-flammable case (PC), high safety

## SPECIFICATION

- ◆ Accuracy:  $\pm 0.03\%$  F.S.
- ◆ Display Screen: High brightness red LED; 20.3mm(0.8")
- ◆ Max. Input Frequency: 10KHz(50% duty cycle)
- ◆ Sampling Cycle: 10 cycles / sec: >10Hz
- ◆ Display Range: 0~99999
- ◆ Over Range Indication: doFL / ioFL
- ◆ Parameters Setting: Push buttons
- ◆ Back Up Memory: EEPROM
- ◆ Alarm Action: " $\geq$  (Hi) on" or "< (Lo) on"
- ◆ Alarm Hysteresis Range: 0~9999
- ◆ Alarm Run Delay Time: 0~9999 sec
- ◆ Relay Contact: AC 250V / 5A; DC 30V / 5A
- ◆ Analog Output Resolution: 16 bit
- ◆ Output Response Time: <250 msec (0~90%)
- ◆ Output Capability: Voltage Output: <20mA  
Current Output: <10V
- ◆ Communication: RS-485 Modbus RTU mode
- ◆ Baud Rate: 19200 / 9600 / 4800 / 2400 bps
- ◆ Operating Temperature: 0~60°C
- ◆ Operating Humidity: 20~90% RH (non-condensing)
- ◆ Storage Temperature: -10~70°C
- ◆ Storage Humidity: 20~90% RH (non-condensing)
- ◆ Power Supply: AC/DC 10~240V, DC22~50V
- ◆ Power Consumption: 3.5VA(2 Relay);3VA(no Relay)
- ◆ Surge Test: 2KVac / 1min (Input / Power)
- ◆ Dimensions: 96(W)\*48(H)\*120(D) mm
- ◆ Weight: About 250 g

## ORDER INFORMATION

TR5 - Code1 - Code2 - Code3

Code1	Input Signal	Code2	Aux. Power	Code3	Output
N5	NPN(5V)	A	AC/DC100~240V	N	None
N2	NPN(12V)	C	DC 22~50V	R1	1 Relay
P5	PNP(5V)			R2	2 Relays
P2	PNP(12V)			V	0~10V
VE	DC 24Vp			A	4~20mA
CT	Contact			Y	RS-485
				O	Option

## WIRING CONNECTION

