


- High brightness 0.32" LCD display: 0~99999999
- Backup memory by replaceable internal battery
- DIN size 24 x 48 mm; easy to install

SPECIFICATION

- ◆ Display Screen: High brightness LCD; 8mm (0.32")
- ◆ Display Range: 0~99999999
- ◆ Back Up Memory: Internal battery, replaceable
- ◆ Temperature Coefficient: 100ppm / °C (0~60°C)
- ◆ Operating Temperature: 0~40°C
- ◆ Operating Humidity: 20~90% RH (non-condensing)
- ◆ Storage Temperature: -10~55°C
- ◆ Storage Humidity: 20~90% RH (non-condensing)
- ◆ Power Supply: Internal battery, replaceable
- ◆ Weight: About 35g

WIRING CONNECTION



ORDER INFORMATION

L248T - Code1

Code1	Display Range		
01	99D. 59H. 59M. 59T	11	99999999H
02	9999D. 59H. 59M.	12	999999M. 59S
03	99D - 59H - 59M	13	999999M - 59S
04	999999D. 59H	14	99999999M
05	999999D. 59H	15	99999999S
06	99999999D		
07	9999H . 59M. 59S		
08	99H - 59M - 59S		
09	999999H. 59M		
10	999999H - 59M		