



- Programmable display by RS-485 communication
- High brightness 0.4" LED display range: -19999~99999; decimal point selectable.
- Communication reading by Master/ writing to slave.
- High stability, non-flammable case (PC) high safety

SPECIFICATION

- ◆ Display Screen: High brightness red LED
10.2mm(0.4")
- ◆ Display Range: -19999~99999
- ◆ Parameters Setting: Push buttons
- ◆ Back Up Memory: EEPROM
- ◆ Communication: RS-485 Modbus RTU mode(Master/Slave)
- ◆ Baud Rate: 19200 / 9600 / 4800 / 2400 bps
- ◆ Temperature Coefficient: 100ppm / °C (0~60°C)
- ◆ Operating Temperature: 0~60°C
- ◆ Operating Humidity: 20~90% RH (non-condensing)
- ◆ Storage Temperature: -10~70°C
- ◆ Storage Humidity: 20~90% RH (non-condensing)
- ◆ Power Supply: AC/DC 100~240V; DC 22~50V
- ◆ Power Consumption: 6.5VA (all functions output)
- ◆ Surge Test: 2KVac / 1min (Input / Power)
- ◆ Dimensions: 96(W)*48(H)*85(D) mm
- ◆ Weight: About 0.3kg

ORDER INFORMATION

VS5 - Code1 - Code2

Code1	Aux. Power	Code2	Communication
A	AC/DC 100~240V	M	Master
C	DC 22~50V	S	Slave

WIRING CONNECTION

